





Optional accessories

Z943SE0 Set of 2 pots and 1 pan Z9914X0 Connecting strip

Induction cooktop with TouchControl.

- $\sqrt{\text{Plug\&Play: No electrician needed.}}$
- $\sqrt{\ }$ Power Boost An extra surge of heat when you need fast results.
- $\sqrt{\,}$ Induction the heat is generated directly in the cookware for precise cooking that stops when power is off.

Features

Technical Data

Product name/family : Cooking zone ceramic

Construction type : Built-in Energy input : Electric

Total number of positions that can be used at the same time : 4 Required niche size for installation (HxWxD) : $51 \times 560-560 \times 10^{-2}$

490-500 mm

Width of the appliance : 592 $\,$ mm $\,$ Dimensions : 51 x 592 x 522 $\,$ mm

Dimensions of the packed product (HxWxD) : $126 \times 753 \times 603$ mm

Net weight : 10.0 kg Gross weight : 11.2 kg

Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Ceramic

Color of surface : Black

Approval certificates : AENOR, CE Length of electrical supply cord : 110 cm

EAN code: 4242004258711

Electrical connection rating : 3700 $\,\mathrm{W}$

Voltage : 220-240 V Frequency : 50; 60 Hz





Features

Flexibility of cooking zones

- 60 cm: space for 4 pots or pans.
- Cooking zone front left: 145 mm, 1.4 KW
- Cooking zone rear left: 180 mm, 1.8 KW (max. power 3.1 KW)
- Cooking zone rear right: 145 mm , 1.4 KW
- Cooking zone front right: 180 mm, 1.8 KW

Usage convenience

- Touch Control Basic: control the power with imprinted +/- touch buttons.
- Variable 9-stage power settings for each zone: precisely adapt the heat with 9 power levels.

Time saving & efficiency

- PowerBoost function in the front left zone
 : boil water faster thanks to 50% more energy than at the highest standard level.
- Quick-Off: quickly switch off a cooking zone with one longer touch.

Design

• Frameless

Safety

- Control panel lock: prevent unintended activation of the hob.
- Main switch: switch off all cooking zones at the touch of a button.
- Safety cut out facility: for safety reasons, heating stops after a preset time if not used (possible to customise).

Installation

- \bullet Dimensions of the product (HxWxD mm): 51 x 592 x 522
- Required niche size for installation (HxWxD mm): 51 x 560 x (490 500)
- Min. worktop thickness: 16 mm
- Connected load: 3.7 KW
- Power cord 1.1 m UK 3 pin plug: plug and play, no electrician required for installation.
- This hob is equipped with a UK 3 pin plug for an easy plug & play installation. The plug limits the maximum power output to 3.7 KW.
 For higher power output, please select a hob without plug and ensure installation is carried out by a qualified electrician.



